

SABS Black® 250/500 MICRONS is manufactured in two variations, namely 250 and 500 microns. The sheeting is suitable for use in limited damp proofing applications in moderate site conditions.

The 250 micron sheeting is available in 2m, 3m, 4m, 6m and 8m widths, while the 500 micron sheeting is available

All our products are tested in our sophisticated test laboratory, on an ongoing basis, according to ISO, SABS and Agrément standards. All our products confirm to the NRCS requirements.



SABS BLACK® 250/500SA							
CERTIFICATION	SANS 952-2016 Type F for use in limited damp proofing applications in moderate site conditions						
MATERIAL	Low-density Polyethylene						
FORM	Roll						
APPEARANCE	Black in colour						
THICKNESS	250 & 500 microns						
ROLL LENGTH	30m						
ROLL WIDTH		1m	2m	3m	4m	6m	8m
ROLL WEIGHT (in kg)	250	7,6	15,2	22,8	30,4	45,6	60,8
	500	-	-	45,6	60,8	91,2	-
	All weights are in accordance with SABS and NRCS requirements						
COMPLIES WITH	NRCS, NHBRC and the National Building Regulations						

All weights are minimum in accordance with SABS and NRCS requirements
Complies with the requirements of: NRCS & NHBRC

INSTALLATION INSTRUCTIONS:

The material is to be laid on a clean surface bed with care taken to ensure no stones or sharp objects which could puncture the sheeting.

The material should not be exposed to direct sunlight for more than a few days.

All joints should be lapped at least 100mm and taped with pressure sensitive tape.